



# Model: Solatube 330 DS-O Open Ceiling (530 mm/21 in. Daylighting System) €€


Project: \_\_\_\_\_ Location: \_\_\_\_\_ Type: \_\_\_\_\_

Product Specifications Appear in US CSI Division 08, Section 08 62 23. For budgeting and quotations use only. Qty: \_\_\_\_\_

Model			Capture Zone			Transfer Zone		Delivery Zone		Options		
<u>S</u>	<u>3</u>	<u>3</u>	<u>0</u>	<u>D</u>	<u>S</u>	-	<u>0</u>	-	<u>D</u>	<u>A</u>	<input type="text"/>	<input type="text"/>
1			2	2a	3	3a	4	4a	5	5a	6	7

## 1 Model

**330 DS-O SolaMaster®** Solatube 330 DS-O (530 mm/21 in. Daylighting System)  
Open Ceiling



## Capture Zone

### 2 Dome





**DA** Dome Acrylic (Meets UFC-ATFP)  
**DP** Dome Polycarbonate (UK Only)

### 2a Dome Options (Leave blank if not desired)

**B** Security Bar      **PB** Dome Edge Protection Band\*  
**SK** Dome Security Kit      **SS** Secondary Diffuser

\*Not for use with Curb Cap Flashing

### 3 Flashings

<b>F4</b> 100 mm Self Mounted		<b>F8</b> 200 mm Self Mounted		<b>F11</b> 275 mm Self Mounted	
<b>FC</b> Curb Cap (Curb by Others)		<b>FSM</b> Metal Roof Flashing			

### 3a Flashing Options (Leave blank if not desired)

**T12\*** Roof Flashing Turret Extension 300 mm/12 in.      **FI** Flashing Insulator  
**T24\*** Roof Flashing Turret Extension 600 mm/24 in.      **CI** Curb Insulator  
**T36\*** Roof Flashing Turret Extension 900 mm/36 in.      **CCI** Curb Cap Insulation  
**T48\*** Roof Flashing Turret Extension 1200 mm/48 in.


\* Specify additional extension tubes in #4

## Transfer Zone

### 4 Extension Tubes Required\*

Run measured from top of flashing to diffuser along centerline of tubing using 600 mm lengths. See 4a for optional 1200 mm length.

- E1\*\*** One Extension Tube – Max Run = 600 mm
- E2\*\*** Two Extension Tubes – Max Run = 1170 mm
- E3\*\*** Three Extension Tubes – Max Run = 1730 mm
- E4\*\*** Four Extension Tubes – Max Run = 2285 mm
- E5\*\*** Five Extension Tubes – Max Run = 2845 mm
- E6\*\*** Six Extension Tubes – Max Run = 3400 mm
- E7\*\*** Seven Extension Tubes – Max Run = 3960 mm
- E8\*\*** Eight Extension Tubes – Max Run = 4520 mm
- E9\*\*** Nine Extension Tubes – Max Run = 5080 mm
- E10\*\*** Ten Extension Tubes – Max Run = 5640 mm
- EXX\*\*** Total Run Length to be Determined by Bidding Contractor



\*At least one 600 mm or 1200 mm extension tube required for diffuser  
\*\*Compatible with dome ring to be used as a top tube or extension tube  
\*\*\*Total tube run will vary depending on flashing used

### 4a Product Options (Leave blank if not desired)

- A1** One 0-90 Degree Extension Tube (Angle Adapter)
- A2** Two 0-90 Degree Extension Tubes (Angle Adapter)
- E** Wire Suspension Kit (15m)
- EL** Optional 1200 mm Extension Tube (Substitute one 1200 mm for two 600 mm above)
- TIP** Thermal Insulation Panel
- AK** 400 mm Top Tube Angle Adapter and 400 mm Bottom Tube Angle Adapter
- TA** 400 mm Top Tube Angle Adapter
- R** Trim Ring

## Delivery Zone

### 5 Diffuser Lens

- L1** OptiView® Diffuser 
- L2** Prismatic Diffuser 

### 5a Options (Leave blank if not desired)

- D** Daylight Dimmer™

### 6 Measurement Standard

- M** Metric
- I** Imperial

## Options

### 7 After Market Accessory Program

- AM** After Market Accessory

### Accessories (Order separately)

- SW** Low voltage switch (white) required to operate Solatube Daylight Dimmers. Note: Only one switch is required per ten (10) synchronously controlled dimmers.
- CA** Two Conductor Low Voltage Cable (150 m)

## Example

### 330 DS-O-DA-F8-E2-L1-D-M

SolaMaster Series® 330 DS-O (530 mm/21 in. Daylighting System), Acrylic Dome, 200 mm High Self Mounted Flashing, Two Extension Tubes, OptiView® Diffuser and Daylight Dimmer. For metric installations.