



Model: Solatube 750 DS-O Open Ceiling (530 mm/21 in. Daylighting System) €


Project: _____ Location: _____ Type: _____

Product Specifications Appear in US CSI Division 08, Section 08 62 23. For budgeting and quotations use only. Qty: _____

Model		Capture Zone				Transfer Zone		Delivery Zone		Options						
<u>S</u>	<u>7</u>	<u>5</u>	<u>0</u>	<u>D</u>	<u>S</u>	-	<input type="text"/>	<input type="text"/>	-	<input type="text"/>	<input type="text"/>	-	<input type="text"/>	-	<input type="text"/>	<input type="text"/>
1		2	2a	3	3a	4	4a	5	5a	6	7					

1 Model

750 DS-O SolaMaster® Solatube 750 DS-O (530 mm/21 in. Daylighting System)
Open Ceiling



Capture Zone

2 Dome






- DA** Acrylic Dome
- DAI** Acrylic Outer Dome + Acrylic Inner Dome
- DPI** Acrylic Outer Dome + Polycarbonate Inner Dome (Required for High Velocity Hurricane Zones)
- MIL** Acrylic Dual Dome (Required for UFC-ATFP)

2a Dome Options (Leave blank if not desired)

- B** Security Bar **PB** Dome Edge Protection Band*
- SK** Dome Security Kit**

* Not for use with Curb Cap Flashing
**Inner dome required for Dome Security Kit

3 Flashings

- | | | | | | |
|--|---|-----------------------------------|---|-----------------------------------|---|
| F4 100 mm
Self Mounted |  | F8 200 mm
Self Mounted |  | F11 275 mm
Self Mounted |  |
| FC Curb Cap
(Curb by Others) |  | FSM Metal Roof
Flashing |  | | |

3a Flashing Options (Leave blank if not desired)

- T12*** Roof Flashing Turret Extension 300 mm/12 in.
- T24*** Roof Flashing Turret Extension 600 mm/24 in.
- T36*** Roof Flashing Turret Extension 900 mm/36 in.
- T48*** Roof Flashing Turret Extension 1200 mm/48 in.
- FI** Flashing Insulator
- CI** Curb Insulator
- CCI** Curb Cap Insulation

* Specify additional extension tubes in #4

Transfer Zone

4 Extension Tubes Required*

Run measured from top of flashing to diffuser along centerline of tubing using 600 mm lengths. See 4a for optional 1200 mm length.

E1** One Extension Tube – Max Run = 600 mm

E2** Two Extension Tubes – Max Run = 1170 mm

E3** Three Extension Tubes – Max Run = 1730 mm

E4** Four Extension Tubes – Max Run = 2285 mm

E5** Five Extension Tubes – Max Run = 2845 mm

E6** Six Extension Tubes – Max Run = 3400 mm


E7** Seven Extension Tubes – Max Run = 3960 mm

E8** Eight Extension Tubes – Max Run = 4520 mm

E9** Nine Extension Tubes – Max Run = 5080 mm

E10** Ten Extension Tubes – Max Run = 5640 mm

EXX** Total Run Length to be Determined by Bidding Contractor



*At least one 600 mm or 1200 mm extension tube required for diffuser

**Compatible with dome ring to be used as a top tube or extension tube

***Total tube run will vary depending on flashing used

4a Product Options (Leave blank if not desired)

A1 One 0-90 Degree Extension Tube (Angle Adapter)

A2 Two 0-90 Degree Extension Tubes (Angle Adapter)

E Wire Suspension Kit (15 m)

EL Optional 1200 mm Extension Tube (Substitute one 1200 mm for two 600 mm above)

TIP Thermal Insulation Panel

AK 400 mm Top Tube Angle Adapter and 400 mm Bottom Tube Angle Adapter

TA 400 mm Top Tube Angle Adapter

R Trim Ring


Delivery Zone

5 Diffuser Lens

L1 OptiView® Diffuser



L2 Prismatic Diffuser



5a Options (Leave blank if not desired)

D Daylight Dimmer™

6 Measurement Standard

M Metric

I

Imperial

Options

7 After Market Accessory Program

AM After Market Accessory

Accessories (Order separately)

SW Low voltage switch (white) required to operate Solatube Daylight Dimmers. Note: Only one switch is required per ten (10) synchronously controlled dimmers.

CA Two Conductor Low Voltage Cable (150 m)

Example

750 DS-O-DPI-F8-E2-L1-M

SolaMaster Series® 750 DS-O (530 mm/21 in. Daylighting System), Acrylic Outer Dome + Polycarbonate Inner Dome, 200 mm High Self Mounted Flashing, Two Extension Tubes and OptiView® Diffuser. For metric installations.